

# Single counterbalance, vented


A-VBSO-SE-CCAP-33-PL-FC2

08.45.92 - X - Y - Z

**RE 18307-54**

Edition: 03.2016


Replaces: 04.2014



## Description

When pressure at V2 rises above the spring bias pressure, the check seat is pushed away from the piston and flow is allowed from V2 to C2. When load pressure at C2 rises above the pressure setting, the relief function is activated and flow is relieved from C2 to V2. With pilot pressure at V1-C1, the pressure setting is reduced in proportion to the pilot ratio, until opening and allowing flow from C2 to V2. The spring chamber is vented to atmosphere allowing operation of all functions independent of back-pressure at V2. For better safety and compact assembly, the C1 and C2 ports are gasket mounted directly on the actuator.

**Note:** port identified with M are not protected with calibrated orifice but in direct connection with pressure channels.



## Technical data


Max. operating pressure	410 bar (5945 psi)
Max. flow	150 l/min. (40 gpm)
Weight	see "Dimensions"
Manifold material	Zinc plated steel
Flange seal kit <sup>1)</sup>	E00000000000057 (R930060587)
Fluid	Mineral oil (HL, HLP) according DIN 51524
Fluid temperature range	-30 °C to 100 (-22 to 212 °F)
Viscosity range	5 to 800 mm <sup>2</sup> /s (cSt)
Recommended degree of fluid contamination	Class 19/17/14 according to ISO 4406
MTTFd	150 years see 18350-51
Other technical data	see data sheet 18350-50
Relief setting:	at least 1.3 times the highest expected load.

The pilot line includes adjustable hydraulic damping, for line tuning of stability and response.

Note: for applications outside these parameters, please consult us.

<sup>1)</sup> Seals for 5 valves.

## Characteristic curve



**Ordering code**

<b>08.45.92</b>	<b>X</b>	<b>Y</b>	<b>Z</b>
-----------------	----------	----------	----------

Single counterbalance, vented

Pilot ratio

**13** 4 : 1

Port sizes	V1 - V2	C1 - C2	M
<b>03</b>	G 1/2	∅ 12 (0.47)	G 1/4
<b>04</b>	G 3/4	∅ 12 (0.47)	G 1/4

SPRINGS		
Adj. pressure range bar (psi)	Pres. increase bar/turn (psi/turn)	Std. setting Q=5 (l/min) bar (psi)
<b>35</b> 150-350 (2200-5000)	110 (1595)	350 (5000)

Pressure setting up to 410 bar: code on request.

Tamper resistant cap code ordering code 11.04.30.001  
Mat. no. R930005194





**Preferred types**

Type	Material number
08459213033500C	R930050625
08459213043500D	R930050627

Type	Material number

**Dimensions**



20 (0.79)	39.5 (1.56)	40 (1.58)	83 (3.27)	86 (3.39)	40 (1.58)	147 (5.79)	16 (0.63)	46 (1.81)	4.6 (0.18)	40 (1.58)	80 (3.15)	10.5 (0.41)			G 3/4	3 (6.6)
20 (0.79)	39.5 (1.56)	40 (1.58)	82 (3.23)	83 (3.27)	39 (1.54)	141 (5.55)	17.5 (0.69)	46 (1.81)	4.6 (0.18)	40 (1.58)	60 (2.36)	10.5 (0.41)			G 1/2	2.3 (5.1)
S1	S	L4	L3	L2	L1	L	I1	I	H2	H1	H	F			Y	Weight kg (lbs)

\* The adjusting screw can be completely unscrewed. Do not exceed the indicated protrusion range of the adjusted screw.

**Bosch Rexroth Oil Control S.p.A.**

Via Leonardo da Vinci 5  
P.O. Box no. 5  
41015 Nonantola - Modena, Italy  
Tel. +39 059 887 611  
Fax +39 059 547 848  
compact-hydraulics-pib@boschrexroth.com  
www.boschrexroth.com/compacthydraulics

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth Oil Control S.p.a.. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging. Subject to change.